
ART 4 PRO





Client:
Project:
Type:
Order Code:
Quantity:

ART 4 PRO is simple, touch based wall-mount DMX controller, designed for RGB and RGBW lighting products. It features a PWM output which can directly drive 12-24VDC LED fixtures, four user programmable static color presets, and a manual speed and dimmer function.

SPECIFICATIONS

DMX Output	4 channels
PWM Output	4 channels, 100W maximum pass through
Interface	Touch senstitve wall panel
Multiple Locations	Use the link out ports to connect up to 32 wall stations and sync preset controls
Audio Indicator	Tone can be toggled on /off by holding buttons 1-4 simultaneously
Operating Voltage	12-24VDC, 500mA (power adapter included - 6W, 12VDC,100-240VAC input)
Mounting	Single gang electrical box (not included)
Finish	White
Material	Aluminum housing, glass panel
	2, 3, 3, 3, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4, 4,
Ambient Operating Temperature	32° F to 104° F (0° C to 40° C)
Ambient Operating Temperature	32° F to 104° F (0° C to 40° C)
Ambient Operating Temperature IP Rating	32° F to 104° F (0° C to 40° C) IP20, dry location
Ambient Operating Temperature IP Rating Fixture Connectors	32° F to 104° F (0° C to 40° C) IP20, dry location Screw terminal block, direct hardwire
Ambient Operating Temperature IP Rating Fixture Connectors Warranty	32° F to 104° F (0° C to 40° C) IP20, dry location Screw terminal block, direct hardwire 2 Years, limited

ART 4 PRO



ORDER CODES

ART4PU: Art 4 Pro (North American Version)

ART4PE: Art 4 Pro (European Version)

INCLUDED COMPONENTS

Power Supplies



APS-6-12

Power Supply for ART 4 Pro 100-240VAC, 500mA, 12VDC, 6W cULus component, CE approved

DIMENSIONS

