



Dyna Flood QA / QW





The **Dyna Flood QA / QW** is a high-power LED flood unit that utilizes Acclaim's quad color technology with your choice or RGBA or RGBW. The Dyna Flood also features an auto switching multi-voltage power supply and on-board touch sensitive menu. It is the perfect solution for dynamic illumination of facades, structures, landscapes, and monuments.


SPECIFICATIONS

| Color | RGBA or RGBW (6000K White) Quad Module |
|-----------------------|--|
| Beam Angle | 20°, 40°, 80°, 20° x 60° |
| Power Consumption | 60W |
| Total Lumens | 1579 @ 20º RGBW |
| Efficacy (Im/W) | 26.3 |
| Lumen Maintenance | 70% @ 150,000 Hours (25° C) |
| Finish | Grey (Standard), Black & White (Optional) |
| Housing | Die Cast Aluminum |
| Operating Temperature | -40°F to 113°F (-40°C to 45°C) |
| Operating Voltage | 100-277VAC, 50/60 Hz |
| Control | DMX-512, 4 DMX Channels Per Fixture |
| Fixture Connectors | 4' IP Rated Power & Signal Cables, Bare End Wires |
| Mounting | Mounts to a Standard 4" Round Electrical Box |
| Rating | IP 66, Wet Location |
| Warranty | 5 Years |
| Weight | 8 lbs. (3.6 kg) |
| Dimensions | W 9.75" x H 9" x L 6.87" (247mm x228 mm x 175 mm) |
| Certifications | .€Dus C€ |

DIMENSIONS








ACCLAIMLIGHTING

Dyna Flood QA / QW

| Client: | |
|-------------|--|
| Project: | |
| Type: | |
| Order Code: | |
| Quantity: | |

ORDER CODES *indicates special order



RELATED COMPONENTS

| DYNAFQWG | Dyna Flood QA / QW Wire Guard |
|-----------|-------------------------------|
| DYNAFGS | Dyna Flood Glare Shield |
| DYNAFEB6 | Dyna Flood Extender Bar 6" |
| DYNAFEB12 | Dyna Flood Extender Bar 12" |
| DYNAFEB36 | Dyna Flood Extender Bar 36" |

WIRING

