

SPECIFIER	
PROJECT	
DATE	

# STAND ALONE DMX CONTROLLER, STICK-GU2







## **PART NUMBER**

SERIES		PROTOCOL		TYPE
LLI-C-CTRL	-	DMX	-	STICK-GU2

### **AVAILABLE MEMORY**


CHANNELS	STEPS
8	1691
16	1011
32	557
48	383
64	291
80	233
96	195
112	166
128	145

## **QUICK SPECIFICATIONS**

	1	
INCLUDED IN PACKAGE	Controller, CD-ROM, USB cable, connector block, power supply	
OS/COMPUTER REQUIREMENTS	Mac OSx 10.6 or higher / Windows XP or higher, USB 2.0 port	
PROGRAM SOFTWARE	Easy Stand Alone, ESA2 (included)	
CONNECTIONS	Power (2 pins), DMX (3 pins), Port (2 pins), Micro-USB Port	
POWER SUPPLY	6VDC power supply (included)	
MOUNTING	Single or double gang wall box	
IP RATING	IP20 - dry locations only	
WARRANTY	5 year limited	

#### **FEATURES**

- Compatible with any DMX LED driver
- Up to 24 dynamic or static scenes
- Wall mounted control panel with glass face, touch-sensitive buttons
- Programmable with included USB cable and software no Ethernet or WiFi required



## STAND ALONE DMX CONTROLLER, STICK-GU2

EXAMPLE WIRING DIAGRAM LED POWER SUPPLY, DECODER, AND LED TAPE SOLD SEPARATELY

