



a brand of TARGETTI

DURATAPE™ RGB IP20 INDOOR

Power Supply (REQUIRED)	Type	Wattage	Input/Output Voltage	Dimmable	IP Rating	Output	Dimensions
DEDD1001244CDMX	ELECTRONIC ADDRESSABLE DMX DRIVER	100W	120-277V / 24V	DMX CONTROL 4 CHANNEL	NEMA1 ENCLOSURE	UL CLASS 2	12" x 12" x 4" ¹
DEDDI2002244CDMX	ELECTRONIC ADDRESSABLE DMX DRIVER	2X100W	120-277V / 24V	DMX CONTROL 4 CHANNEL	NEMA1 ENCLOSURE	UL CLASS 2	12" x 12" x 4" ¹
DEDDxxxDMX consult factory	ELECTRONIC ADDRESSABLE DMX DRIVER STANDALONE, UL LISTED ENCLOSURE PROVIDED BY OTHERS	consult factory	120-277V / 24V	DMX DIMMING	N/A	UR CLASS 2	consult factory

¹ Dimensions include enclosure with mounting bracket.

* Constant voltage drivers 50/60HZ, voltage regulated with short circuit protection. Operating temperature -40 C- 80° C

* Installation of power supply must be compliant to Class 2 installation standards. Refer to NEC and local building code requirements.

MAXIMUM INTERCONNECTED TAPE LENGTH PER DRIVER

Fixture Wattage	Driver Wattage							
	40W	60W	96W	90W	2X90W	3X90W	100W	2X100
3.5W/ft	9FT	13FT	21FT	20FT	(2) 20FT	(3) 20FT	22FT	(2) 22FT

Controller (Optional)	Type	Application	Voltage	Listing	Dimensions	# Ouput Channels	Number of Zones	Number of Scenes
SWITCH20	RGBW Touch DMX512 Wall Control Panel with Sensitive Glass Touch Panel, White Finish	Indoor Only	12-24V DC	UL	4.73"H x 2.95"W x 1.15"D	12	3	1
TGDMXSLESAU9	Stand-alone DMX Programmable Controller with Easy to Use Software Interface	Indoor Only	5.5V DC	ETL, UL	5.3"W x 5.5"H x 1.9D	256	1	20



SWITCH20



TGDMXSLESAU9