



a brand of TARGETTI


INTELLISTRAND CABLE LIGHT

KEY FEATURES

- Low voltage cable light for indoor / outdoor lighting applications, perfect for festoon mounting, taught or swayed.
- 16 gauge conductive cable with factory attached sockets.
- Available in full dynamic 24 bit color changing RGB, individually addressable spheres for dramatic full color lighting effects.
- Lamp spacing available in 12" OC and 24" OC.
- Flat base can be easily mounted against a wall or ridged surface.
- Max continuous length: 75' max per run (12" OC)
150' max per run (24" OC)
- Multiple dimming options available, see power supply selections.



DIMENSIONAL DRAWING




DETAILS

- Spacing** 12" or 24" OC Socket Spacing
- Color Temp** RGB dynamic color changing
- Wattage** 11W per socket
- Installation** Attach to aircraft cable (sold separately) and to be secured with cable ties (provided by others). Optional cable wrap encases aircraft cable and Intellistrand cable for a clean one wire look (see page 3).
- Weight** 0.25Lbs/socket
- Power Supply** Listed Class 2 output, 24 VDC power supply required
- IP Rating** IP65
- Certifications** cETLus Class 2 Wet Listed 4007019
Tested in accordance with LM-79-08
Energy efficient for California installations.
- Warranty** 5 year warranty

INSTALLATION EXAMPLES


Facade



Swayed



Straight



FIXTURE DATA

Model	Efficacy* Lm/Wt	Lm/Bulb	Wt/ Globe
RGB	40.91	45	11

PRODUCT CODE	TYPE	WATTAGE	COLOR TEMP	SOCKET SPACING	VOLTAGE	+	POWER SUPPLY
IN — Intellistrand	CL — Cable Light	1 — 1.1W	FC — RGB	12 — 12" OC 24 — 24" OC	24 — 24VDC		


Fixture is project specific and manufactured to order, longer lead times may be expected based on a project by project basis. Consult factory for more information.




a brand of TARGETTI

INTELLISTRAND CABLE LIGHT


CONNECTION CABLES (REQUIRED)




INTEL09
Lead cable 10ft length with 2-pole female connector, black finish.




INTEL19
Lead cable 20ft length with 2-pole female connector, black finish.




INTEL06
Lead cable 3ft length with 4-pole female connector, black finish.




INTEL33
Lead cable 20ft length with 4-pole female connector, black finish.




INTEL66
Jumper cable 8ft length with 1ea 4-pole female connector and 4-pole male connector, black finish.




INTEL31
Jumper cable 16ft length with 1ea 4-pole female connector and 4-pole male connector, black finish.



INTEL07
T-split cable with 1ea 4-pole female connector, 4-pole male connector and 2-pole male connector, black finish.



INTEL32
T-split cable with 2ea 4-pole female connectors and 1ea 4-pole male connector, black finish.



INTEL08
End Cap 4-Pole Male Connector, black finish.



a brand of TARGETTI

INTELLISTRAND CABLE LIGHT

Power Supply (REQUIRED)	Type	Wattage	Input/Output Voltage	Dimmable	IP Rating	Output	Dimensions
DMLE301242UD	EMCOD MLE-UD ELECTRONIC DRIVER WITH WIRING COMPARTMENT.	30W	120-277V / 24V	FWD / REV PHASE / TRIAC / 0-10V / PWM	NEMA3R ENCLOSURE	UL CLASS 2	4.47" X 6.79" X 1.38"
DMLE601242UD	EMCOD MLE-UD ELECTRONIC DRIVER WITH WIRING COMPARTMENT.	60W	120-277V / 24V	FWD / REV PHASE / TRIAC / 0-10V / PWM	NEMA3R ENCLOSURE	UL CLASS 2	4.47" X 6.79" X 1.38"
DMLE961242UD	EMCOD MLE-UD ELECTRONIC DRIVER WITH WIRING COMPARTMENT.	96W	120-277V / 24V	FWD / REV PHASE / TRIAC / 0-10V / PWM	NEMA3R ENCLOSURE	UL CLASS 2	5.16" X 7.73" X 1.54"
DMLE1922242UD	EMCOD MLE-UD ELECTRONIC DRIVER WITH WIRING COMPARTMENT.	2X96W	120-277V / 24V	FWD / REV PHASE / TRIAC / 0-10V / PWM	NEMA3R ENCLOSURE	UL CLASS 2	5.04" X 10.94" X 1.81"
DMLE2882242UD	EMCOD MLE-UD ELECTRONIC DRIVER WITH WIRING COMPARTMENT.	3X96W	120-277V / 24V	FWD / REV PHASE / TRIAC / 0-10V / PWM	NEMA3R ENCLOSURE	UL CLASS 2	5.04" X 10.94" X 1.81"
DELV30124DJBX	MAGNITUDE SOLIDRIVE ELECTRONIC DRIVER WITH BUILT-IN JUNCTION BOX.	30W	120-277V / 24V	0-10V 1%	IP66	UL CLASS 2	12.1" X 2.36" X 1.4"
DELV30124D	MAGNITUDE SOLIDRIVE ELECTRONIC STANDALONE DRIVER. UL LISTED ENCLOSURE PROVIDED BY OTHERS.	30W	120-277V / 24V	0-10V 1%	IP66	UR CLASS 2	7.5" X 2.36" X 1.4"
DELV60124DJBX	MAGNITUDE SOLIDRIVE ELECTRONIC DRIVER WITH BUILT-IN JUNCTION BOX.	60W	120-277V / 24V	0-10V 1%	IP66	UL CLASS 2	12.1" X 2.36" X 1.4"
DELV60124D	MAGNITUDE SOLIDRIVE ELECTRONIC STANDALONE DRIVER. UL LISTED ENCLOSURE PROVIDED BY OTHERS.	60W	120-277V / 24V	0-10V 1%	IP66	UR CLASS 2	7.5" X 2.36" X 1.4"
DELV96124DJBX	MAGNITUDE SOLIDRIVE ELECTRONIC DRIVER WITH BUILT-IN JUNCTION BOX.	96W	120-277V / 24V	0-10V DIMMING 1%	IP66	UL CLASS 2	12.1" X 2.36" X 1.4"
DELV96124D	MAGNITUDE SOLIDRIVE ELECTRONIC STANDALONE DRIVER. UL LISTED ENCLOSURE PROVIDED BY OTHERS.	96W	120-277V / 24V	0-10V DIMMING 1%	IP66	UR CLASS 2	7.5" X 2.36" X 1.4"
DEL60PWM	ELECTRONIC PWM DRIVER STANDALONE, UL LISTED ENCLOSURE PROVIDED BY OTHERS	60W	120-277V / 24V	0-10V/PWM 10%	IP67	UR CLASS 2	5.9" X 2.09" X 1.38"
DELI601241CPWM	ELECTRONIC PWM DRIVER	60W	120-277V / 24V	0-10V/PWM 10%	NEMA1 ENCLOSURE	UL CLASS 2	10" x 10" x 4" ¹
DEL90PWM	ELECTRONIC PWM DRIVER STANDALONE, UL LISTED ENCLOSURE PROVIDED BY OTHERS	90W	120-277V / 24V	0-10V/PWM 10%	IP67	UR CLASS 2	6.73" X 2.48" X 1.48"
DELI901241CPWM	ELECTRONIC PWM DRIVER	90W	120-277V / 24V	0-10V/PWM 10%	NEMA1 ENCLOSURE	UL CLASS 2	10" x 10" x 4" ¹
DELI1802242CPWM	ELECTRONIC PWM DRIVER	2X90W	120-277V / 24V	0-10V/PWM 10%	NEMA1 ENCLOSURE	UL CLASS 2	12" x 12" x 4" ¹
DELI2703243CPWM	ELECTRONIC PWM DRIVER	3X90W	120-277V / 24V	0-10V/PWM 10%	NEMA1 ENCLOSURE	UL CLASS 2	12" x 12" x 4" ¹

¹ Dimensions include enclosure with mounting bracket.

* Constant voltage drivers 50/60HZ, voltage regulated with short circuit protection. Operating temperature -40 C- 80° C

* Installation of power supply must be compliant to Class 2 installation standards. Refer to NEC and local building code requirements.

* Consult factory for additional driver options (ie: DMX, DALI, wattage, size, shape, Lutron, ELDO, or others).



a brand of TARGETTI

INTELLISTRAND CABLE LIGHT

Controller (Optional)	Type	Application	Voltage	Listing	Dimensions	# Ouput Channels	Number of Zones	Number of Scenes
SWITCH20	RGBW Touch DMX512 Wall Control Panel with Sensitive Glass Touch Panel, White Finish	Indoor Only	12-24V DC	UL	4.73"H x 2.95"W x 1.15"D	12	3	1
TGDMXSLESAU9	Stand-alone DMX 1/2 Universe Programmable Controller with Easy to Use Software Interface	Indoor Only	5.5V DC	ETL, UL	5.3"W x 5.5"H x 1.9D	256	1	20
TGDMXSLESAUE7	Stand-alone DMX 2 Universe Programmable Controller with Easy to Use Software Interface	Indoor Only	5V DC	ETL, UL	5.3"W x 5.5"H x 1.9D	1024	5	250



SWITCH20



TGDMXSLESAU9



TGDMXSLESAUE7

MOUNTING ACCESSORIES (OPTIONAL)



DLDC1AC1/16SS

1/16" inch (diameter) Aircraft cable stainless steel. For use up to 70lbs load, 7 x 7 SS T304 with a minimum break strength at 480lbs.

DLDC1AC3/32SS

3/32" inch (diameter) Aircraft cable stainless steel. For use up to 150lbs load, 7 x 7 SS T304 with a minimum break strength at 900lbs.



DLDSLWRAP

1/2" Diameter black spiral cable wrap for use with aircraft cable. To encase aircraft cable and DuraLED Light Cable for a clean 1 wire look, sold per foot. **(1.5ft of Wrap needed to span evenly per 1ft of cable)**




a brand of TARGETTI

INTELLISTRAND CABLE LIGHT



SYSTEM LAYOUT EXAMPLE DIAGRAM

RGB Dynamic Color Changing



POSSIBLE CONFIGURATIONS

RGB Dynamic Color Changing





a brand of TARGETTI

INTELLISTRAND CABLE LIGHT

PHOTOMETRY

