



RGBW COLOR CHANGING (OUTDOOR)


CONSTANT CURRENT | RUBBER COATED

LINEAR LED LIGHTING


Fixture Type: _____

Project: _____


Location: _____



RGBW-1



RGBW-2 & RGBW-3



PRODUCT FEATURES

- 90+ CRI
- Dimmable
- 50,000 hour life
- 5-year warranty
- UL-listed for indoor and outdoor use
- 3M™ industrial adhesive backing
- Constant Current
- For use with electronic power supplies

SPECIFICATIONS

Input Voltage	24V DC / Constant Voltage
Beam Spread	120°
Max Run Length	Unlimited, power feed every 96W
Production Intervals (RGBW-1)	2.438" (62mm)
Production Intervals (RGBW-2 & 3)	3.938" (100mm)
Lumens	425 max. lm/ft
CRI	3000K = 90+
Diode	5050
Dimming Options	RF, WiFi, DMX
Temp Range	-40°F (-40°C) to 149°F (65°C)
Rating	IP67


RGB COLOR SPECTRUM



ORDERING INFORMATION

Series	Max Run	Watts	Lumens
1	12.5 ft	7.7W	425 lm/ft
2	25 ft	3.8W	340 lm/ft
3	50 ft	1.9W	250 lm/ft

Example: **RGBW-3-WR-24V**



Conforms to ANSI/UL Standard 2108
Certified to CAN/CSA Standard C22.2 No. 250.0

